



GENERAL SPECIFICATIONS:

STANDARD-DUTY STRAIGHT TRACK

Provide **Model 101S** as manufactured by H & H Specialties Inc., South El Monte, CA.

Track shall be 16 gauge galvanized steel, roll-formed to 1-3/4" wide X 2" high with continuous slot in bottom. Provide unspliced in lengths up to 26'.

Suspend track with two-piece clamp hanger formed from 11 gauge steel. Provide 2' overlap at center, rigidly separated by two overlap clamps. Install end stop with cord support at each overlapping track end. Where lengths exceed 26', connect tracks with 12" long, two-piece splicing clamp of 12 gauge steel.

Provide single carriers, spaced on 12" centers, constructed of two polyethylene wheels fastened parallel to formed steel carrier body with swivel hook for attachment of curtain.

Master carriers shall be 4-wheel assemblies with formed steel bodies and two swivel hooks each. Connect to operating line with two machined steel cord clamps captured within each body.

Single and double end pulleys shall clamp securely to the underside of the track channel and shall contain 2-1/2" diameter sheaves enclosed in steel housings to prevent operating line from escaping the grooves. Nylatron GS sheaves shall be molded around shielded and greased ball bearings and grooved to accommodate up to 1/4" operating line.

Provide floor block in 12 gauge steel housing containing 4" Nylatron GS shielded ball bearing sheave. Sheave axle shall lock at any point within 9" vertical slots to allow tension adjustment of operating line.

Black operating line shall be 1/4" diameter, stretch-resistant rope with spun polyester outer jacket braided over solid aramid core.

All steel components shall be zinc plated to resist corrosion.
